

Response to review comment

Comments	Response
Coastal inundation methodology	
Section 2.1 – The use of LiDAR DEMs (where available) and satellite DEM products (where LiDAR is not available) is appropriate until there is further LiDAR captured across the region. NIWA have appropriately noted the uncertainties associated with the data.	agreed
Section 2.3 – T+T agree with the methodology for calculating extreme sea levels. MSL offsets and storm tide values are sensible and are based on the best available information.	agreed
Section 2.3.3 – Wave setup assessment:	
TC Fehi was used as a benchmark event, but the components of the observed water level during Fehi are not presented, neither were the offshore wave conditions during the event. What was the max observed level of debris and what was the contribution of storm surge, tide, river flow, and wave setup?	The different component of the total water level for Fehi are presented in details in section 2.7.2 (storm tide ~ = 2.4m LVD and ave setup 0.6m at high tide and 0.8m during low tide). We have added more information on the wave setup analysis.
What is the ARI of a 4.5 m wave? We would expect 50- and 100-year wave height is much higher – which means there could be a small under prediction when representing an extreme future event?	Based on Godoi et al. analysis. 4.5m is the mean annual maxima for significant wave height. The 1% AE _p is 5-6m on the west coast
Is there is spatial variation in wave height / setup across the region, like there is with storm tide?	No, because of the lack of accurate hindcast at a scale relevant for we used a constant wave setup across the whole region. Ideally future hindcast can produce a joint probability with a spatially variable storm tide and wave setup contribution. More information was added
There is not much detail on the wave climate that influences coastal erosion and inundation hazards. This could be included in background, with sections on the typical and extreme conditions.	Agreed we've added some more information in the paragraph

Section 2.4 – T+T agree with the 0.2 m SLR increment approach instead of tying SLR values to specific projections. The report clearly outlines the benefits of this approach.	Noted
Section 2.6 – The inundation has been assessed using the bathtub approach (except at Orowaiti Lagoon where hydrodynamic modelling has been undertaken). T+T agree that a bathtub approach is suitable for identifying areas of land susceptible to coastal inundation. The report clearly outlines the limitations associated with bathtub mapping.	Noted
Section 2.7 – There is not much detail on the Orowaiti hydrodynamic model: – It would be useful to include a figure of the model domain and boundary processes in Section 2.7. – XBeach is mentioned for generating the ocean boundary signal, but it does not appear XBeach was used to run the model (since setup is added separately). What model was used (assuming BG Flood?) What was the spectral Hs and Tp used to generate the surfbeat signal? – ‘The wave setup was then added as an additional shift so that the maximum ESL matches the values in Table 2-3. With the training wall extending beyond the surf zone, the forcing for the Buller River mouth does not include wave setup.’ – This sounds sensible; however it would be useful to include a schematic of this on the model domain map. – Is setup included for the Orowaiti lagoon mouth? – Comparison of hydrodynamic model with observations is very good and provides confidence in the method.	Agreed. A paragraph was added to describe the model. Most of the required details to the model are provided in Gardner 2017 and in the note accompanying the report.
Coastal erosion methodology	
Section 3.1 – There is an inconsistency with the terms ‘zones’ and ‘areas’ used throughout the report. T+T note that ‘zones’ tend to be used in a planning context and areas or lines in a hazard assessment context	Agreed. We have changed the use of “zones” and “area” throughout the document to be more consistent.

Section 3.1 – The formula provided to assess the erosion hazard is a relatively dated version. MfE (2017) and Envirolink (2013) outline more contemporary formula for defining the erosion hazard.	Agreed, however the essential components are the same. The formula here is used to describe the component of the analysis that use a probabilistic approach.
Section 3.1 – Hybrid-probabilistic approach has been adopted to manage the uncertainty associated with the data. A normal distribution is assumed for all terms and where there is lack of data the distributions are based on expert knowledge and approximation. T+T agree with this approach, however, it would be useful to see the distributions/values adopted for each site. It is unclear if a single distribution has been used for long-term and SLR components ('r') or a distribution for each	The distribution are specific to each transect and difficult to represent without overwhelming the report. Details to try to summarize the result for each priority area. Details were added to the methodology text to confirm the distribution used to account for acceleration of SLR.
Section 3.1.1 – T+T consider the manual review/correction of hazard lines to account for geomorphical features and underlying geology is important, given the varied morphologies along this coastline. T+T suggest adding a statement that only unconsolidated shorelines have been assessed (i.e. beaches) and consolidated shorelines (i.e. banks and cliffs) have not been considered.	Added a statement to confirm the erosion analysis is only for unconsolidated shorelines.
Section 3.2 – T+T agree digitized shorelines from historic aerials is suitable to assessing trends in shoreline movement. However, it is unclear how the shoreline is defined on the gravel beaches. Is the back of the barrier the same as the vegetation line (i.e. Rapahoe example)? Also, section 4.1.3 notes that 1878 cadastral charts were used. There is high uncertainty around this shoreline data and what features the mapped shoreline represent	Noted. Back of gravel barrier is used where it is detectable otherwise vegetation line is used. Add a statement to section 3.2.1 to clarify that. I agreed with the caution with the cadastral map. For cadastral as well as aerial imagery a component of uncertainty in georeferencing and in the quality of the digitized line has been used. This is accounted for in the trend analysis so it does not weight as much as say the high res 1940s aerial pictures or 2014 satellite imagery. We believe the section 3.2.1 highlight that uncertainty well. We have also added a registry of summary of assumption in table 5.1 that includes a statement about georeferencing and digitizing.

<p>Section 3.2.2 – There appears to be an inconsistent approach for protection structures. Some structures are excluded, some are included and some are partially included. In some locations with private structures, the impact of SLR has been excluded (i.e. Granity school, Hector). This may not be an appropriate approach as there is uncertainty around if the structures will be maintained and upgraded in the future. There is also mention of the rock revetment near Rapahoe being destroyed during Ex TC Fehi which highlights why structures might need to be excluded from the assessment. It may be useful to provide a map at each site which shows the location of known structures. If feasible, then an estimate of erosion hazard in absence of structures (i.e. based on values from adjacent unprotected sites), would be appropriate and useful for adaptation and planning purposes.</p>	<p>Agreed. We added a segment in section “3.4 Treatment of coastal defence structures”. Only a few locations in this analysis were considered with suitable rock revetment (and may not need a map.). These are listed in section 3.4. The section also includes detail about what treatment is done for protected shorelines to include a measure of residual risk.</p>
<p>Section 3.2.2 – T+T agree with the Bruun rule for assessing shoreline response to SLR. However, it is unclear what values have been used for the closure depths and do these differ between the MSG beach and a sandy beach? It could be useful to provide values for the adopted closure slopes/depths.</p>	<p>Agreed. Section 3.2.2 was amended to include details of distribution for depth of closure calculations.</p>
<p>Section 3.3 – Roll-over (short-term retreat) has been assessed based on judgement and field observations. We consider this is reasonable given the lack of profile data available. However, a berm ‘roll-over’ response may not be applicable for the sandy beaches (ie. Beach Road, CHA 3). Storm cut/erosion of the dune toe is likely to be more appropriate for sandy beaches.</p>	<p>Agreed although the underlying treatment remains the same we rename this section 3.3 Short-term retreat Roll-over (Short-term Roll-over /storm cut).</p>
<p>Section 3.3 – 30 m sounds reasonable for an upper bound storm cut distance on the sandy open coast. However, it is unclear what the 30 m is set back from on the gravel beaches? Is it the berm crest? Or back of the gravel barrier?</p>	<p>Back of the barrier. We added this detail in section 3.3.</p>

Section 4.3.3 – Report states “For the coastal erosion hazard zone, the structure only prevents acceleration in the rate of erosion from acceleration of sea level rise. The recent historical erosion rate is maintained in the calculation to account for failure of the structure.” This needs further explanation.	Agreed. Original statement in the report was wrong. We added a whole section to detail the treatment in the presence of structures.
Section 4.7.3 – The probabilistic erosion assessment has not been completed for the Haast Jackson Bay Road due to the nature of the site. A ‘low-lying near-coast’ hazard zone has been adopted instead. It is unclear what defines this zone? What elevation and shoreline proximity?	The zone was defined as a fixed distance from the coast. This was added to the text
Section 4.7.4 – As above, for the Jackson Bay village.	Same as above
Section 6 – The summary states that 50-year and 100-year outlooks have been mapped. What probabilities and SLR scenarios have been used to define these lines?	Only lines for the 95 th percentile outlook are being used. This was added to the text
Equation numbers and referencing need to be checked throughout the document.	Agreed. We have now fixed this issue
There are several typos that have been noted within the attached marked-up PDF document.	Thanks. We have addressed these throughout the document